


VST - GE / VSTI - GE Plugs


Dimensions in mm

Hex head Plug with Elastomeric seal as per DIN 3852, Part 11
Male BSPP (G) threads as per ISO 228



Part No.	G Male BSPP thread	Ød4	i	L1	S1
VSTG01E	G 1/8 A	14	8	14.5	14
VSTG02E	G 1/4 A	19	12	20	19
VSTG03E	G 3/8 A	22	12	22.5	22
VSTG04E	G 1/2 A	27	14	24	27
VSTG06E	G 3/4 A	32	16	26	32
VSTG08E	G 1 A	40	16	27	41
VSTG10E	G1.1/4 A	50	16	28	50
VSTG12E	G1.1/2 A	55	16	30	55

Socket head Plug with Elastomeric seal as per DIN 3852, Part 11
Male BSPP (G) threads as per ISO 228



Part No.	G Male BSPP thread	Ød4	i	L1	S3
VSTIG01E	G 1/8 A	14	8	13	5
VSTIG02E	G 1/4 A	19	12	17	6
VSTIG03E	G 3/8 A	22	12	17	8
VSTIG04E	G 1/2 A	27	14	20	10
VSTIG06E	G 3/4 A	32	16	22	12
VSTIG08E	G 1 A	40	16	24	17
VSTIG10E	G1.1/4 A	50	16	24	22
VSTIG12E	G1.1/2 A	55	16	24	24

Standard material : Carbon Steel

For Stainless steel material, add prefix 316 - to the part code Example : 316 - VSTIG04E

Standard surface treatment : Chrome free Alkaline Zinc Plating.

For Zinc Nickel surface treatment, add suffix - ZnNi Example : VSTIG04E - ZnNi